

Winter 3-9-2016

Electric field effects on grain boundary formation and grain growth

Klaus van Benthem

University of California, Davis, benthem@ucdavis.edu

Hasti Majidi

University of California, Davis

Jorgen Rufner

University of California, Davis

Wei Qin

University of California, Davis

Follow this and additional works at: http://dc.engconfintl.org/efa_sintering



Part of the [Engineering Commons](#)

Recommended Citation

[1] H. Majidi, T.B. Holland, K. van Benthem, Quantitative analysis for in situ sintering of 3% yttria-stabilized zirconia in the transmission electron microscope, *Ultramicroscopy*. 152 (2015) 35–43. doi:10.1016/j.ultramic.2014.12.011. [2] H. Majidi, K. van Benthem, Consolidation of Partially Stabilized ZrO₂ in the Presence of a Noncontacting Electric Field, *Phys. Rev. Lett.* 114 (2015) 195503. doi:10.1103/PhysRevLett.114.195503. [3] J.F. Rufner, R. Castro, K. van Benthem, Electric field effects on the sintering of magnesium aluminate nanoparticles, in: American Ceramic Society, Chicago, IL, 2012.

ELECTRIC FIELD EFFECTS ON GRAIN BOUNDARY FORMATION AND GRAIN GROWTH

Klaus van Benthem, University of California, Davis

Benthem@ucdavis.edu

Hasti Majidi, University of California, Davis

Jorgen Rufner, University of California, Davis

Wei Qin, University of California, Davis

Key Words: TEM, EFAS, defect formation, activation energy, grain growth, spinel, YSZ

The application of electric fields can enable the accelerated consolidation of materials during field assisted sintering, such as spark plasma sintering or flash sintering. Although such techniques are already employed for the synthesis of a wide variety of microstructures with unique macroscopic properties, a fundamental understanding of the atomic-scale mechanisms for grain boundary formation and subsequent migration in the presence of electrostatic potentials is mostly absent from the literature. We have designed experiments to specifically de-couple the effects of heating and applied electrostatic fields during consolidation. In situ transmission electron microscopy studies were carried out with new sample holder designs to investigate densification and grain growth mechanisms in the absence and presence of electrical fields [1,2]. Quantitative experimental observations reveal lowering of activation energies for both densification [2] and grain growth [3] as a consequence of the applied electric field strength. In the specific case of flash sintering, microstructural characterization furthermore reveals that electrode effects can lead to non-homogeneous microstructure evolution during processing. Examples for yttrium-stabilized ZrO_2 and MgAl_2O_4 spinel will be discussed.

This research is supported by the University of California Laboratory Fee Program (12-LR-238313) and the US Army Research Office (program manager: Dr. D. Stepp) under grant W911nf-12-1-0491-0.

References:

- [1] H. Majidi, T.B. Holland, K. van Benthem, Quantitative analysis for in situ sintering of 3% yttria-stabilized zirconia in the transmission electron microscope, *Ultramicroscopy*. 152 (2015) 35–43. doi:10.1016/j.ultramic.2014.12.011.
- [2] H. Majidi, K. van Benthem, Consolidation of Partially Stabilized ZrO_2 in the Presence of a Noncontacting Electric Field, *Phys. Rev. Lett.* 114 (2015) 195503. doi:10.1103/PhysRevLett.114.195503.
- [3] J.F. Rufner, R. Castro, K. van Benthem, Electric field effects on the sintering of magnesium aluminate nanoparticles, in: American Ceramic Society, Chicago, IL, 2012.