

Fall 11-10-2015

Constructing nanocrystal-in-glass composites for smart windows

Delia Milliron

The University of Texas Austin, milliron@che.utexas.edu

Follow this and additional works at: http://dc.engconfintl.org/composites_all



Part of the [Materials Science and Engineering Commons](#)

Recommended Citation

Delia Milliron, "Constructing nanocrystal-in-glass composites for smart windows" in "Composites at Lake Louise (CALL 2015)", Dr. Jim Smay, Oklahoma State University, USA Eds, ECI Symposium Series, (2016). http://dc.engconfintl.org/composites_all/63

This Conference Proceeding is brought to you for free and open access by the Proceedings at ECI Digital Archives. It has been accepted for inclusion in Composites at Lake Louise (CALL 2015) by an authorized administrator of ECI Digital Archives. For more information, please contact franco@bepress.com.

CONSTRUCTING NANOCRYSTAL-IN-GLASS COMPOSITES FOR SMART WINDOWS

Delia J. Milliron
Department of Chemical Engineering
The University of Texas at Austin
Austin, Texas, USA
+1-512-232-5702
milliron@che.utexas.edu

The integration of inorganic nanocrystals as building units into mesoscale architectures yields materials wherein the components and their interfaces are both essential in defining structure and function. Randomly mesostructured nanocrystal-in-amorphous niobia composites can be formed by chemically linking niobium polyoxometalate (POM) clusters to colloidal nanocrystals in the solution phase. When films of these assemblies are thermally annealed, the clusters undergo condensation. They cross-link to form a continuous amorphous niobia matrix surrounding, and covalently linked to, the embedded nanocrystals. The resulting composite materials combine intrinsic characteristics of each component and exhibit unique functionality that we ascribe to reconstruction at the nanocrystal-glass interface. An architected nanocomposite can instead be formed when the arrangement of the nanocrystals into a mesoporous framework is accomplished first, using a block copolymer template. In this case, POMs are in-filled in a second step, then annealed to form the nanocrystal-niobia glass composite. Our composite metal oxide thin films exhibit a unique optical switching response to electrochemical reduction. Namely, they independently control the transmittance of visible and near infrared light as a function of voltage. These results highlight the tremendous opportunity to tune structure at both the atomic and nanometer length scales to realize new functionality.