

Fall 11-10-2015

# Laser-based three-dimensional printing of zirconium oxide hybrid materials

Roger Narayan  
UNC

Follow this and additional works at: [http://dc.engconfintl.org/composites\\_all](http://dc.engconfintl.org/composites_all)



Part of the [Materials Science and Engineering Commons](#)

---

## Recommended Citation

Roger Narayan, "Laser-based three-dimensional printing of zirconium oxide hybrid materials" in "Composites at Lake Louise (CALL 2015)", Dr. Jim Smay, Oklahoma State University, USA Eds, ECI Symposium Series, (2016). [http://dc.engconfintl.org/composites\\_all/70](http://dc.engconfintl.org/composites_all/70)

This Conference Proceeding is brought to you for free and open access by the Proceedings at ECI Digital Archives. It has been accepted for inclusion in Composites at Lake Louise (CALL 2015) by an authorized administrator of ECI Digital Archives. For more information, please contact [franco@bepress.com](mailto:franco@bepress.com).

# LASER-BASED THREE-DIMENSIONAL PRINTING OF ZIRCONIUM OXIDE HYBRID MATERIALS

Roger Narayan, UNC/NCSU Joint Department of Biomedical Engineering

Key Words: two photon polymerization, zirconium oxide hybrid materials, three-dimensional scaffolds

We have recently examined use of an additive manufacturing approach known as two-photon polymerization to create structures out of zirconium oxide hybrid materials for medical device applications. Two photon polymerization involves processing of a structure with sub-microscale features in an additive manner directly from a computer-generated model. In two-photon polymerization, a femtosecond laser beam is focused within a small volume in a near infrared light-transparent photosensitive material; nearly simultaneous absorption of two photons within a small volume in the photosensitive material results in polymerization and hardening of the material. Because of the quadratic dependence of two-photon absorption probability on intensity, photopolymerization occurs in a localized volume. The energy associated with two photon absorption of infrared photons is analogous to the energy associated with a single photon in the ultraviolet light region of the electromagnetic spectrum. The unit volume of material polymerized using two-photon polymerization is known as a voxel (volumetric pixel). The minimum size of the features obtained in a two-photon polymerization-fabricated structure is related to the voxel-voxel distance, the photosensitivity of the material, the numerical aperture of the objective lens, the exposure time, and the laser power. Titanium:sapphire femtosecond lasers are used in two photon polymerization since these lasers produce high energy intensity in the focal volume due to their short pulse width and high peak power.

A medically-relevant structure with an arbitrary geometry may be created using two photon polymerization by polymerizing the material along the laser trace, which is translated in three dimensions via a micropositioning system. Two photon polymerization exhibits advantages over conventional mechanisms for scalable production of small-scale medical devices. Several classes of inexpensive inorganic-organic hybrid materials, polymers, and other photosensitive materials may be fabricated via two photon polymerization. Two photon polymerization can be set up in a conventional environment; no specialized facilities (e.g., cleanroom facilities) are needed. In comparison with conventional multiple-step medical device processing techniques, two photon polymerization is a rapid, straightforward, single-step process. Two photon polymerization was used to create scaffolds for tissue engineering with linear designs in a layer-by-layer manner out of a zirconium oxide hybrid material. Good feature-to-feature uniformity within the scaffolds. In vitro cell studies were used to examine cell-scaffold interactions over time.